

Indirect (for use with gas/oil/LPG boiler)					
Model	Vented or Unvented	Diameter	Height	Weight Empty	Weight Full
MX-120-IND-582	Unvented	582 mm	986mm	35kg	155Kg
MX-150-IND-582	Unvented	582 mm	1166mm	38Kg	188Kg
MX-180-IND-582	Unvented	582 mm	1346mm	42Kg	212Kg
MX-210-IND-582	Unvented	582 mm	1526mm	45Kg	255Kg
MX-250-IND-582	Unvented	582 mm	1766mm	51Kg	301Kg
MX-300-IND-582	Unvented	582 mm	2066mm	55Kg	355Kg
MX-120-IND-485	Unvented	485 mm	1250mm	33kg	151kg
MX-150-IND-485	Unvented	485 mm	1440mm	37kg	184kg
MX-180-IND-485	Unvented	485 mm	1690mm	41kg	208kg
MX-210-IND-485	Unvented	485 mm	2000mm	45kg	242kg
Direct (for use in electric only properties via immersion heaters)					
Model	Vented or Unvented	Diameter	Height	Weight Empty	Weight Full
MX-120-ELE-582	Unvented	582 mm	986mm	35kg	155kg
MX-150-ELE-582	Unvented	582 mm	1166mm	38kg	188kg
MX-180-ELE-582	Unvented	582 mm	1346mm	42kg	212kg
MX-210-ELE-582	Unvented	582 mm	1526mm	45kg	255kg
MX-250-ELE-582	Unvented	582 mm	1766mm	51kg	301kg
MX-300-ELE-582	Unvented	582 mm	2066mm	55kg	355kg
MX-400-ELE-710	Unvented	710 mm			
MX-120-ELE-485	Unvented	485 mm	1250mm	33kg	151kg
MX-150-ELE-485	Unvented	485 mm	1440mm	37kg	184kg
MX-180-ELE-485	Unvented	485 mm	1690mm	41kg	208kg
MX-210-ELE-485	Unvented	485 mm	2000mm	45kg	242kg
Indirect - PVE (for use with gas/oil/LPG boiler) with Mixergy PV Diverter module					
Model	Vented or Unvented	Diameter	Height	Weight Empty	Weight Full
MX-120-IND-582-PVE	Unvented	582 mm	986mm	35kg	155kg
MX-150-IND-582-PVE	Unvented	582 mm	1166mm	38kg	188kg
MX-180-IND-582-PVE	Unvented	582 mm	1346mm	42kg	212kg
MX-210-IND-582-PVE	Unvented	582 mm	1526mm	45kg	255kg

MX-250-IND-582-PVE	Unvented	582 mm	1766mm	51kg	301kg
MX-300-IND-582-PVE	Unvented	582 mm	2066mm	55kg	355kg
MX-120-IND-485-PVE	Unvented	485 mm	1250mm	33kg	151kg
MX-150-IND-485-PVE	Unvented	485 mm	1440mm	37kg	184kg
MX-180-IND-485-PVE	Unvented	485 mm	1690mm	41kg	208kg
MX-210-IND-485-PVE	Unvented	485 mm	2000mm	45kg	242kg
Direct - PVE (for use in electric only properties via immersion heaters) with Mixergy PV Diverter module					
Model	Vented or Unvented	Diameter	Height	Weight Empty	Weight Full
MX-120-ELE-582-PVE	Unvented	582 mm	986mm	35kg	155kg
MX-150-ELE-582-PVE	Unvented	582 mm	1166mm	38kg	188kg
MX-180-ELE-582-PVE	Unvented	582 mm	1346mm	42kg	212kg
MX-210-ELE-582-PVE	Unvented	582 mm	1526mm	45kg	255kg
MX-250-ELE-582-PVE	Unvented	582 mm	1766mm	51kg	301kg
MX-300-ELE-582-PVE	Unvented	582 mm	2066mm	55kg	355kg
MX-120-ELE-485-PVE	Unvented	485 mm	1250mm	33kg	151kg
MX-150-ELE-485-PVE	Unvented	485 mm	1440mm	37kg	184kg
MX-180-ELE-485-PVE	Unvented	485 mm	1690mm	41kg	208kg
MX-210-ELE-485-PVE	Unvented	485 mm	2000mm	45kg	242kg
Accessories					
SKU	Description				
KIT-HEATPUMP-02	Heat Pump Kit incl. plate heat exchanger, pump, controls interface and fittings				
MAS0086-01	3rd Party PV diverter connection kit				
iHP integrated heat pump cylinder					
R290 Variant					
SKU	Description	Diameter	Height	Weight Empty	Weight Full
MX-120-IH2-579	120L Integrated HP R290 Smart Cylinder	580mm	1325mm	83Kg	203Kg
MX-150-IH2-579	150L Integrated HP R290 Smart Cylinder	580mm	1515mm	86Kg	236Kg
MX-180-IH2-579	180L Integrated HP R290 Smart Cylinder	580mm	1695mm	90Kg	270Kg
MX-210-IH2-579	210L Integrated HP R290 Smart Cylinder	580mm	1885mm	94Kg	304Kg
MX-250-IH2-579	250L Integrated HP R290 Smart Cylinder	580mm	2145mm	97Kg	347Kg